

**DESCRIPTION**

**A-GS, A-180 – GS Pulling Tool**

The GS Pulling Tool is a basic wireline device which connects a wireline tool string to a wireline retrievable flow control device that is to be run into or retrieved from a well. The GS Running/Pulling Tool is designed to engage an internal type fishing neck. The tool is offered in a wide range of sizes. The tools are supplied for standard or H<sub>2</sub>S service.

GS Running Tool is used to deploy the subsurface flow control devices.

**DIMENSIONAL SPECIFICATIONS**

Nominal Size	OD	Reach	Will Engage	Fishing Neck	Connection
1.250 in.	1.160 in.	1.080 in.	0.880 in.	1.000 in.	5/8 in. 11 UN
1.500 in. / 1.750 in.	1.470 in.	1.620 in.	1.060 in.	1.187 in.	15/16 in. 10 UN
2.000 in.	1.750 in.	0.620 in.	1.380 in.	1.375 in.	15/16 in. 10 UN
2.000 in.	1.810 in.	1.620 in.	1.380 in.	1.375 in.	15/16 in. 10 UN
2.500 in.	2.160 in.	1.620 in.	1.810 in.	1.750 in.	15/16 in. 10 UN
2.500 in.	2.250 in.	1.620 in.	1.810 in.	1.750 in.	15/16 in. 10 UN
3.000 in.	2.720 in.	1.620 in.	2.310 in.	2.313 in.	1 1/16 in. 10 UN
3.500 in.	3.110 in.	1.620 in.	2.620 in.	2.313 in.	1 1/16 in. 10 UN
4.000 in.	3.620 in.	1.620 in.	3.120 in.	2.313 in.	1 1/16 in. 10 UN

Note: Other sizes available on request.

