

DESCRIPTION

A-RRT, A-203 – R Running Tool

R Running Tool. It is used to run. The fishing neck is connected to the device to improve the industry standard connections.

R Running Tool is used to deploy flow control devices e.g. R and RN lock mandrels by locating and set in respective selective or bottom No-Go type Lock mandrels.

DIMENSIONAL SPECIFICATIONS

Size	OD	Fishing Neck	Connection
inch	inch	inch	
1.375	1.281	1.000	5/8-16 UN
1.500	1.469	1.187	15/16-10 UN
1.710	1.641	1.187	15/16-10 UN
1.781	1.750	1.375	15/16-10 UN
1.875	1.750	1.375	15/16-10 UN
2.000	1.938	1.375	15/16-10 UN
2.125	2.062	1.375	15/16-10 UN
2.188	2.172	1.750	15/16-10 UN
2.313	2.172	1.750	15/16-10 UN
2.500	2.360	1.750	15/16-10 UN
2.562	2.172	1.750	15/16-10 UN
2.875	2.840	2.313	1 1/16-10 UN
3.250	3.190	2.312	1 1/16-10 UN
3.500	3.125	2.313	1 1/16-10 UN
3.437	3.406	2.313	1 1/16-10 UN
3.630	3.600	2.313	1 1/16-10 UN
3.688	3.625	2.313	1 1/16-10 UN
3.750	3.688	2.313	1 1/16-10 UN
3.813	3.750	2.313	1 1/16-10 UN
4.000	3.938	2.313	1 1/16-10 UN
4.125	3.938	2.313	1 1/16-10 UN
4.313	4.281	2.313	1 1/16-10 UN

Note: Other sizes available on request.

